

ISONEM[®] BE 89



Liquid Rubber Membrane

ISONEM BE 89 is a 700% elastic liquid rubber coating. After drying, it forms a waterproof coating on applied surfaces. This coating keeps its property between -20 and + 80 degrees; is not affected by UV and sun. It is used safely even in places exposed to sun such as terraces and roofs. High elasticity and crack hiding property. Suitable for insulations of old or new roofs and use under the ground; but not affected by underground waters. It strongly adheres to dry or slightly moist surfaces. It does not swell or separate over time. Resistant to the plant roots. Also suitable for use in garden terraces.

USAGE AREAS:

- On exterior walls of basement and on foundation walls
- In old or new terraces and roofs,
- In places such as garden terraces, balconies,
- In re-insulation of bitumen surfaces,
- On the membranes or in repairs,
- In roof slots,
- In insulation of concrete pipe, brick, metal, wood, zinc, gas concrete etc surfaces,
- In protecting all kinds of concrete surfaces against corrosion.

USAGE TYPE:

Preparation of Surface: The application surfaces must be dry or slightly moist. It must not be used in subbasements having salt efflorescence or in insulations from negative sides. Ensure that the surfaces are clean and free of particles such as dirt, rust, mud etc. Pits, holes, cracks and segregations must be repaired with ISONEM M 03 by applying ISONEM D 10 LATEX. If there is dilation, dilation insulation must be made with ISONEM A4 beforehand.

PRIMER APPLICATION:

ISONEM BE 89 as a primer is diluted with water at a ratio of 1:1. It is let absorb on the surface with a stiff brush. Let it dry fully. Before this process, R- 3 cm chamfer must be beveled on bottoms of wall and parapet in terrace and roof applications. In terrace and roof applications, ISONEM GS 98 must absolutely be laid and the application must be done with this. In foundation walls or grounds, there is no need for the glass fiber mesh.

APPLICATION TYPE:

ISONEM BE 89 is ready to use. However, before application it must be mixed homogeneously. After primer process, ISONEM BE 89 is applied on the surface in 2-3 layers with a brush or a roller without a dilution by waiting among layers to dry. Every time, the application must be made in perpendicular layers to each other. It is recommended to apply by using ISONEM GS 98 between layers in terraces, roofs or breakable floors. The application must not be made in extreme temperatures or frost. In summer, we recommend applications in the mornings or in the evenings. Make sure that the roof is sloped correctly in application roofs. Having water outlets and preventing the water to form a pond on the roof must be regarded.

CONSUMPTION: 1-1,5 kg/m² (primer + 3 layers)

PACKING: 18 kg plastic pail

STORAGE CONDITIONS/SHELF LIFE: 12 months from date of production if stored properly in unopened and undamaged original sealed containers at temperatures between +5°C to +35°C at dry conditions. Protect from excessive temperature and frost.



The information contained in this leaflet has been prepared to our best knowledge, and in consistency with the results of our experiments and experience, and are the products of our know-how based on our accumulation of decades. However, the application of our products accurately and successfully, is entirely beyond our control and responsibility. Therefore, the scope of our liability is limited to the quality of our products and this technical leaflet supercedes all the previous technical leaflets and all the explanations and the information contained in the product labels.