

# ISONEM<sup>®</sup> BETON PAINT



## Beton Floor Paint

ISONEM BETON PAINT is a product, which can be produced as one-component color or transparent for porous surfaces such as concrete, screed, asphalt, paving stone, etc., that has been developed as an alternative to the epoxy and polyurethane based floor coverings. It features UV and weather resistance, high wear resistance, fast drying and durability. It well penetrates and holds on to the application surfaces. It is easy to apply. Thanks to its high mechanical resistance, it creates a long lasting film on the surfaces. Yellowing, fading or lifting off over time does not occur. It is wear resistant and not effected by the human and vehicle traffic. It is waterproof and resistant to various chemicals.

### AREAS OF USAGE:

- Concrete, screed, asphalt, paving stones,
- Parking and garages,
- Factory and warehouse floors
- Traffic islands and roadsides, curbs for marking,
- Pool sides, tourist facilities, bicycle paths, coastlines, walkways, squares, parks and gardens.

### METHOD OF APPLICATION:

Application surface must be clean and dry. Do not apply on damp and wet surfaces. Do not apply on the surfaces, where water and water vapor pressure from the negative side and salt efflorescence are present. Oily and dirty surfaces must be cleaned by solvent-based cleaners.

**Application:** Apply with a brush, roller or by spraying in two coats. After the first coat fully dries (around 4 hours), finish the application by applying ISONEM BETON PAINT. Protect the newly applied surface from dirt, dust, water and rain until a through-dry state.

**CONSUMPTION:** Depending on absorbency of the surface and color, 200 - 250 gr/m<sup>2</sup> (2 coats)

**PACKAGING:** 18 kg in tin buckets

**STORAGE:** 12 months in its original unopened package in a cool and dry environment.

