

# ISONEM<sup>®</sup> MS 82



## Anti-Moisture Paint

ISONEM MS 82 is a very strong insulation paint that is manufactured through modification with special chemicals and polymers for the purpose of the elimination of the problems caused by moisture and humidity on the interior and exterior walls of the buildings arising from the natural conditions. The product can be applied on all types humid or dry walls, and painted and non-painted surfaces. Due to its perfect resistance against alkali, it guarantees the prevention of moisture on the walls. Its adherence resistance on all surfaces is extremely strong. The product shows a high resistance against chemicals. It is not affected from UV radiation, rain, water or salts. It is applicable on the interior and exterior walls of the buildings, foundations, basements, garages and cellars, interior walls facing north, and many other areas that are exposed to moisture and humidity. It forms highly water resistant film layers on the surfaces where it is applied. It adheres very strongly on the surfaces, even if the paint or the wall is humid, dries very fast and ensures perfect insulation. It is not effected from salt water and salt vomits. Due to this characteristic, it is also used in the elimination of blistering in the foundations of the building. While **ISONEM MS 82** provides a waterproof layer on the surfaces where it is applied, it also penetrates into the walls and dries up the humidity inside the walls with the special chemicals in its ingredients. Through this way, it ensures dryness inside the wall. **ISONEM MS 82** paints do not cause any side effects. Therefore, it never damages the surface or the materials on which it is applied.

### USING AREAS:

- On moist walls,
- On painted or non painted walls affected by humidity
- On the interior and exterior walls of the foundation
- On the walls of the basement floor
- On surfaces and floors coated with plaster, concrete, alum, etc
- In tunnels, on the walls of buildings facing north
- In the elimination of problems arising from humidity and moist.

### TECHNICAL PROPERTIES:

- **Color:** White
- **Drying time:** 24 hours
- **Application temperature:** Between + 5°C - 35°C
- **Resistance to water pressure:** 4 psi (0.28 kg / cm<sup>2</sup>)

### APPLICATION:

ISONEM MS 82 anti-moisture paint is ready to use, and does not require primer. The surfaces where the product will be applied, may be moist or humid. It can be applied on all types of surfaces, whether painted or not. Only if the surface to be painted has swollen areas, such areas must be cleaned. After opening the lid of **ISONEM MS 82** in its original package, stir the product thoroughly well for 3 minutes. After stirring, apply the first layer on the surface with a brush, pistol spray or roll. Wait for 24 hours after applying the first layer, then apply the second layer. Make sure that the area where the paint is applied is thoroughly ventilated and use protective mask, gloves and goggles during application.

**CONSUMPTION:** 500 gr/m<sup>2</sup>

**PACKAGING:** 5 kg metal container.

**STORAGE CONDITIONS/SHELF LIFE:** 12 months from date of production if stored properly in unopened and undamaged original sealed containers at temperatures between +5°C to +35°C at dry conditions. Protect from excessive temperature and frost.



The information contained in this leaflet has been prepared to our best knowledge, and in consistency with the results of our experiments and experience, and are the products of our know-how based on our accumulation of decades. However, the application of our products accurately and successfully, is entirely beyond our control and responsibility. Therefore, the scope of our liability is limited to the quality of our products and this technical leaflet supercedes all the previous technical leaflets and all the explanations and the information contained in the product labels.